

150-31090

Article Number: 150-31090

Description: Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26" - .28", Height .4", PA66HS, Black, 500/pkg



Base Data	Local Order Number	150-31090
	Type	T30RFT6LG
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• Fir tree design can be used with a wide variety of applications.</li> <li>• Disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</li> <li>• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.
	Short Description	Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26" - .28", Height .4", PA66HS, Black, 500/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		133N
Length L (Imperial)		6.0"
Length L (Metric)		150mm
Length L2 (Imperial)		0.46"
Length L3 (imperial)		0.69"
Length L3 (metric)		17.5mm
Fixation Method		Fir Tree
Identification Plate Position		none
Length L2 (Metric)		11.6mm
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated

150-31090



Product Dimensions	Width W (Imperial)	0.14"
	Width W (Metric)	3.5mm
	Width W2 (Imperial)	0.4"
	Width W2 (Metric)	9.0mm
	Width W3 (Imperial)	0.19"
	Width W3 (Metric)	5.0mm
	Height H (Imperial)	0.04"
	Height H (Metric)	1.2mm
	Height H2 (Imperial)	0.4"
	Height H2 (Metric)	11.1mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	5.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	6.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.75mm
	Mounting Hole Diameter D (Imperial)	0.26 - 0.28"
	Mounting Hole Diameter D (Metric)	6.4 - 7.1 mm
	Mounting Hole Diameter D Min. (Imperial)	0.256"
	Mounting Hole Diameter D Max. (Imperial)	0.276"
	Thickness T (Imperial)	0.043"
	Thickness T (Metric)	1.1mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes

150-31090



Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	1.5kg