

598-00339

Article Number: 598-00339

Description: Wire Marker Tape #1, .25" x 1.25", #9, White, 1/pkg



Base Data	
Local Order Number	WMT9
Type	WMT
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> <li>• Dispenser protects unused markers until needed.</li> <li>• Each marker is pre-cut for easy dispense and removal.</li> <li>• Markers are coated to protect the printed text from chemicals and abrasion.</li> <li>• Dispenser is refillable making it a cost effective and efficient marking system.</li> </ul>
Quantity Per	box
Product Description	The Wire Marker Tape dispenser is a plastic label dispensing container that provides a convenient, economical system for wire marking. HellermannTyton's wire marker tape features sharp, crisp, pre-printed legends where are coated to resist smearing and abrasion. Each marker is provided on a carrier strip that prevents adhesive contamination prior to installation, assuring permanent, non-flagging marker ends.
Short Description	Wire Marker Tape #1, .25" x 1.25", #9, White, 1/pkg
Product Dimensions	
Length L (Imperial)	1.25"
Length L (Metric)	31.75mm
Cable Diameter Min. (Metric)	0.00mm
Width W (Imperial)	0.25"
Width W (Metric)	6.35mm
Height H (Imperial)	1.25"
Height H (Metric)	31.75mm
Bundle Diameter Min. (Imperial)	0.1"
Bundle Diameter Min. (Metric)	2.54mm
Bundle Diameter Max. (Imperial)	0.375"
Bundle Diameter Max. (Metric)	9.52mm
Outside Diameter Min. (Imperial)	0.1"
Outside Diameter Min. (Metric)	2.54mm

598-00339



Product Dimensions	Outside Diameter Max. (Imperial)	0.375"
	Outside Diameter Max. (Metric)	9.52mm
Material and Specifications		
	Material	Tyvek
	Material Shortcut	Tyvek
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +248°F (-40°C to +120°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +248°F (-40°C to +120°C)
ROHS Compliant	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	1
	Package Quantity (Metric)	1
	Customs Number(Schedule B)	3919102055