

Tripp Lite
1111 W. 35th Street

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

4-Port 1U Rack-Mount USB/PS2 KVM Switch with On-Screen Display

MODEL NUMBER: B042-004







Description

Tripp Lite's NetController 4-Port, 1U rackmount KVM Switch is an affordable, highly-flexible enterprise class KVM Switch, which allows the user to connect either USB or PS/2 keyboards and mice. In addition, P780-Series USB/PS2 combo KVM cable kits allow you to connect either USB or PS/2 computers, without the need to purchase separate cables or adapters. Control up to 4 directly connected computers, or expand the number of connected computers to up to 244 by daisychaining up to 15 additional B042-Series KVM switches. Switch between connected computers via the On-Screen Display (OSD), pushbuttons, or keyboard hotkey commands. Other features include: password protection, auto-scanning, auto-logout, firmware upgrade and video support up to 2048 x 1536 (QXGA). Mounts easily in a standard 19" rack/cabinet and includes all necessary mounting hardware. Compatible with all major operating systems. Constructed of heavy-duty steel housing.

Features

- NetController 4-Port, 1U rackmount KVM switch
- Control 4 computers via a single VGA monitor and USB or PS/2 keyboard/mouse
- P780-Series USB/PS2 combo KVM cable kits allow you to connect either USB or PS/2 computers, without the need to purchase separate cables or adapters
- Control up to 244 computers by daisychaining up to 15 additional B042-Series KVM switches
- Allows for easy customization of ports by daisy-chaing any combination of B042-Series KVM's (4-, 8- or 16-port)
- Standard 19" Rackmount size hardware included
- On-Screen Display (OSD) menu for intuitive operation and easy control
- · Switch between connected computers via the On-Screen Display (OSD), pushbuttons, or keyboard hotkey commands
- Supports video resolution up to 2048 x 1536
- · Password protection and auto-logout features
- Firmware upgradeable
- Robust metal case design ensures best EMI/RFI shielding and video quality

Highlights

- NetController 4-Port, 1U rackmount KVM switch
- Control 4 computers via a single VGA monitor and USB or PS/2 keyboard/mouse
- Control up to 244 computers by daisychaining up to 15 additional B042-Series KVM switches
- P780-Series USB/PS2 combo KVM cables kits allow you to connect either USB or PS/2 computers, without the need to purchase separate cables or adapters
- Compatible with all major operating systems

Package Includes

- B042-004 NetController 4-Port,
 1U rackmount KVM switch
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.3A / Output: 9V, 1A)
- Rackmount hardware
- 8 In. Daisychain cable (for longer daisy-chain cables, see Tripp Lite P781 series cables)
- Daisychain terminator
- 4 ft. HD15 to DB9 firmware upgrade cable
- CD with owner's manual and quick start guide
- Quick start guide

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234



- Hot-swappable: disconnect and reconnect USB computers without rebooting
- Supports standard 5-button Microsoft, Logitech, or comparable mice
- Supports standard Microsoft, Logitech, or comparable keyboards
- Compatible with all major operating systems
- Constructed of heavy-duty steel housing

Specifications

OVERVIEW Users 1 AC Adapter Input: 100-240V, 50/60Hz, 0.3A / Output: 9V, 1A Console No Max CPU 244 PHYSICAL Color Black LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable ENVIRONMENTAL BTUs 245.52 COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cats KVM Switch No WARRANTY Product Warranty Period (Worldwide) 1-year limited warranty	-	
Input: 100-240V, 50/60Hz, 0.3A / Output: 9V, 1A	OVERVIEW	
Console No Max CPU 244 PHYSICAL Color Black LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable ENVIRONMENTAL BTUS 245.52 COMMUNICATIONS PORT Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cats KVM Switch No	Users	1
PHYSICAL Color Black LCD Monitor (in.) Not Applicable LCD Monitor (em) Not Applicable ENVIRONMENTAL BTUs 245.52 COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cats KVM Switch No	AC Adapter	Input: 100-240V, 50/60Hz, 0.3A / Output: 9V, 1A
PHYSICAL Color Black LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable ENVIRONMENTAL BTUs 245.52 COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cats KVM Switch No	Console	No
Color Black LCD Monitor (in.) Not Applicable LCD Monitor (cm) Not Applicable ENVIRONMENTAL BTUs 245.52 COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat S KVM Switch No	Max CPU	244
LCD Monitor (in.) Not Applicable ENVIRONMENTAL BTUS 245.52 COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat S KVM Switch No	PHYSICAL	
LCD Monitor (cm) Not Applicable ENVIRONMENTAL BTUs 245.52 COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cats KVM Switch No WARRANTY	Color	Black
ENVIRONMENTAL BTUS 245.52 COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	LCD Monitor (in.)	Not Applicable
BTUS 245.52 COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	LCD Monitor (cm)	Not Applicable
COMMUNICATIONS Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	ENVIRONMENTAL	
Port Control Push Buttons, Hotkeys, OSD IP Remote Access No CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	BTUs	245.52
CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	COMMUNICATIONS	
CONNECTIONS Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	Port Control	Push Buttons, Hotkeys, OSD
Ports 4 PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	IP Remote Access	No
PC/Server Connections VGA; USB; PS/2 SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	CONNECTIONS	
SPECIAL FEATURES Cat5 KVM Switch No WARRANTY	Ports	4
Cat5 KVM Switch No WARRANTY	PC/Server Connections	VGA; USB; PS/2
WARRANTY	SPECIAL FEATURES	
	Cat5 KVM Switch	No
Product Warranty Period (Worldwide) 1-year limited warranty	WARRANTY	
	Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies