

157-00035



Article Number: 157-00035

Description: Wide Strap Cable Tie with 8mm Stud Mount, 12.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag

|                                   |                       |  |
|-----------------------------------|-----------------------|--|
| Base Data                         | Local Order Number    | 157-00035  |
|                                   | Type                  | WSI8MM   |
|                                   | Color                 | Black (BK)   |
|                                   | Features and Benefits | <ul style="list-style-type: none"> <li>• Mount provides low insertion and high extraction forces which makes for a strong and easy installation.</li> <li>• Clamping rails increase grip on round bundles.</li> <li>• Thinner strap provides increased flexibility for improved ergonomics.</li> <li>• Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.</li> </ul> |
|                                   | Quantity Per          | bag  |
|                                   | Product Description   | Wide Strap Heavy Duty Cable Ties features a stud mount for direction application onto a 8 mm threaded stud. The tie is 0.5" wide, and handles bundles from 0.38" - 4.2". The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud.   |
|                                   | Short Description     | Wide Strap Cable Tie with 8mm Stud Mount, 12.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag  |
|                                   | Product Dimensions    | Minimum Tensile Strength (Imperial)  |
| Minimum Tensile Strength (Metric) |                       | 534N   |
| Length L (Imperial)               |                       | 12.7"  |
| Length L (Metric)                 |                       | 322.6mm  |
| Fixation Method                   |                       | Weld Stud Fixing   |
| Identification Plate Position     |                       | none   |
| Releasable Closure                |                       | No   |
| Tie Closure                       |                       | plastic pawl   |
| Variant                           |                       | Inside Serrated  |
| Width W (Imperial)                |                       | 0.5"   |
| Width W (Metric)                  |                       | 12.7mm   |
| Bundle Diameter Min. (Imperial)   |                       | 0.38"  |
| Bundle Diameter Min. (Metric)     |                       | 9.5mm  |

157-00035



|                             |                                 |  |
|-----------------------------|---------------------------------|--|
| Product Dimensions          | Bundle Diameter Max. (Imperial) | 3.2"   |
|                             | Bundle Diameter Max. (Metric)   | 82.5mm   |
|                             | Stud Size (Imperial)            | 0.315"   |
|                             | Stud Size (Metric)              | 8.0 mm   |
| Material and Specifications |                                 |  |
|                             | Material                        | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
|                             | Material Shortcut               | PA66HIRHSUV  |
|                             | Flammability                    | UL 94 HB   |
|                             | Operating Temperature           | -40°F to +230°F (-40°C to +110°C)  |
|                             | REACH Compliant (Article 33)    | Yes  |
|                             | ROHS Compliant                  | Yes  |
| Logistic and Packaging      |                                 |  |
|                             | Package Quantity (Imperial)     | 300  |
|                             | Package Quantity (Metric)       | 300Bag   |
|                             | Customs Number(Schedule B)      | 3926909987   |
|                             | Content Unit (BMEcat)           | pieces   |