


ELECTRICAL:

CURRENT RATING: 5 AMPS
CONTACT RESISTANCE: 15 mOhms Max.
INSULATION RESISTANCE: 1,000 MOhms min.
VOLTAGE: 500VAC FOR 1 MINUTE

TEMPERATURE: -50° C TO 125° C

ROHS COMPLIANT

DO NOT SCALE FROM DRAWING



DRAWN:
PAM JENKINS

CHECKED:

DATE:
8-18-98

DATE:

NorComp

N. | SCALE: | SHEET | OF | REV | 1:1 | 1 | 2 | 8


DWG NO. 170-YYY-17YL000

DESCRIPTION: CLINCH NUT HARDWARE


TOLERANCE: ALL DIMENSIONS ARE ±0.010

ALL CLINCH-NUTS ARE 4-40 INTERNAL THREADS


01X 0.065" (BOARD SIDE) - CN1



02X 0.236" (BOARD SIDE) - CN2



03X..... 0.236" (MATING SIDE) - CN8



DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

C. SMITH

CHECKED:

DATE:

DATE:

DATE:

SCALE:

SHEET

OF

REV

2

8

DWG NO. 170-YYY-17YL000

FULL

ROHS COMPLIANT