

170-03065

Article Number: 170-03065



Description: Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 50 ft/reel

Base Data	Local Order Number	170-03065
	Type	BSHTTST134SR
	Color	Silver (SR)
	Features and Benefits	<ul style="list-style-type: none"> <li>• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li> <li>• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li> <li>• Cuts with ordinary scissors for fast, easy application.</li> </ul>
	Quantity Per	reel
	Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
	Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 50 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		15.2m
Reel Length (imperial)		50.0ft
Bundle Diameter Max. (Imperial)		1.687"
Bundle Diameter Max. (Metric)		42.8mm
Nominal Diameter (Imperial)		1-3/4"
Nominal Diameter (Metric)		44.5mm
Material and Specifications	Material	Aluminum (AL)
	Material Shortcut	AL
	Flammability	non flammable
	Operating Temperature	-76°F to +491°F (-60°C to +255°C)

170-03065



Material and Specifications	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50ft
	Package Quantity (Metric)	15.24m
	Customs Number(Schedule B)	7019901000
	Weight (imperial)	3.70lbs
	Weight (Metric)	1.68kg