

596-00823

HellermannTyton

Article Number: 596-00823

**SISTEMA FOTOVOLTAICO
EQUIPADO CON
DESCONEXIÓN RÁPIDA**

Description: Solar Label, Reflective, Spanish, PHOTOVOLTAIC SYSTEM...RAPID SHUTDOWN, 5.5" x 1.75", Red, 50/pkg

Base Data	Local Order Number	596-00823
	Type	PSEWRSS
	Color	Red (RD)
	Features and benefits	<ul style="list-style-type: none"> • Made with UV-stable inks and materials for durability and weather resistance. • Reflective properties to meet applicable NEC code requirements for reflective identification. • Supplied with an aggressive adhesive to ensure long life. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
	Quantity Per	roll
	Product Description	HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, Reflective, Spanish Version, "PHOTOVOLTAIC SYSTEM EQUIPPED WITH RAPID SHUTDOWN", 5.5" X 1.75", Red
	Local Order Number 2	English Version: 596-00474
	Short Description	Solar Label, Reflective, Spanish, PHOTOVOLTAIC SYSTEM...RAPID SHUTDOWN, 5.5" x 1.75", Red, 50/pkg
	Product Dimensions	Length L (Imperial)
Length L (Metric)		139.7mm
Width W (Imperial)		5.5"
Width W (Metric)		139.7mm
Height H (Imperial)		1.75"
Height H (Metric)		44.45mm

596-00823



Material and Specifications		
	Material	Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate
	Material Shortcut	242/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	UL969
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055
	Labels per Column	1
	Labels per Row	1