

155-30602



Article Number: 155-30602

Description: Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg

Base Data	Local Order Number	155-30602
	Type	T50SSBS5OT-E
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Design gives quick and easy assembly by hand without the need for tools. • Mount can be used in a wide variety of applications where 5mm weld studs or 5mm ISO bolts. • Design provides low insertion force and high extraction force.
	Quantity Per	bag
	Product Description	The Standoff Stud Mount tie applies easily to weld studs and secures bundles away from fixing holes. These are used primarily in the automotive industry, but can be used in a variety of applications.
	Short Description	Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		200N
Length L (Imperial)		6.0"
Length L (Metric)		160mm
Fixation Method		Weld Stud Fixing
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.18"
Width W (Metric)		4.6mm
Bundle Diameter Min. (Imperial)		0.16"
Bundle Diameter Min. (Metric)		4.0mm
Bundle Diameter Max. (Imperial)		1.4"

155-30602



Product Dimensions	Bundle Diameter Max. (Metric)	35.0mm
	Stud Length Max. (Imperial)	0.65"
	Stud Length Max. (Metric)	16.5mm
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.35mm
	Stud Size (Imperial)	0.2"
	Stud Size (Metric)	5.0 mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	2.3kg