


553-50025

Article Number: 553-50025

Description: Heat Shrink Labels, .38" (9.52mm), Single Sided, 1-Slit, PO-X, White, 500/box



Base Data	
Local Order Number	553-50025
Type	HST9-3WH-S
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> <li>• Slide Slit and optional center slits for easy wire insertion.</li> <li>• Smooth surface for clean and legible printing.</li> <li>• Supplied on a ladder style carrier so that markers can be kitted after printing.</li> <li>• A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.</li> </ul>
Quantity Per	box
Product Description	HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.
Short Description	Heat Shrink Labels, .38" (9.52mm), Single Sided, 1-Slit, PO-X, White, 500/box
Product Dimensions	
Length L (Imperial)	0.597"
Length L (Metric)	15.16mm
Printable (Yes/No)	Yes
Variant	Thin-Wall
Width W (Imperial)	0.95"
Width W (Metric)	24mm
Height H (Imperial)	0.597"
Height H (Metric)	15.16mm
Diameter Min. (Imperial)	9.52"
Diameter Max. (Imperial)	0.375"
Outside Diameter Max. (Imperial)	0.375"
Outside Diameter Max. (Metric)	9.52mm
Wall Thickness WT (Imperial)	0.031"

553-50025



Product Dimensions	Wall Thickness WT (Metric)	0.79mm
	Flexibility	Flexible
	Print Method	Thermal transfer
	Recovered Diameter d (metric)	3.1mm
	Recovered Diameter d (imperial)	0.122"
	Supplied Diameter D (imperial)	0.354"
	Supplied Diameter D (metric)	9.0mm
	Thickness T (Metric)	3.0µm
	Width of Liner WL (imperial)	3.0"
	Width of Liner WL (metric)	76.2mm
	Width of Printable Area (imperial)	0.95"
	Width of printable area (metric)	24.10mm
	Material and Specifications	
Material		Polyolefin, cross-linked (PO-X)
Material Shortcut		PO-X
Dielectric Strength (Metric)		19.7 kV min.
Flammability		UL 224 VW-1
Shrink Temperature		+194 °F (+90 °C)
Operating Temperature		-67°F to +275°F (-55°C to +135°C)
REACH Compliant (Article 33)		Yes
ROHS Compliant		Yes
Certification/Specification	SAE - AS81531	
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Markers per row	2
	Content Unit (BMEcat)	pack
	Weight (imperial)	0.93lbs
	Weight (Metric)	0.43kg