

150-55948

Article Number: 150-55948

Description: Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .17"-.20", Max Bundle 1.4", PA46, Grey, 500/pkg



Base Data	
Local Order Number	150-55948
Type	T30RFT5
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> <li>• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.</li> <li>• Initial fir tree serves as a locating feature for assistance in blind assembly applications.</li> <li>• Disc feature provides anti-rattle protection in high vibration applications.</li> </ul>
Quantity Per	bag
Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.
Short Description	Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .17"-.20", Max Bundle 1.4", PA46, Grey, 500/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	30.0lbs
Minimum Tensile Strength (Metric)	135N
Length L (Imperial)	6.0"
Length L (Metric)	150mm
Length L2 (Imperial)	0.5"
Length L3 (imperial)	0.52"
Length L3 (metric)	13.2mm
Fixation Method	Fir Tree
Identification Plate Position	none
Length L2 (Metric)	11.6mm
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14"

150-55948



Product Dimensions	Width W (Metric)	3.5mm
	Width W2 (Imperial)	0.4"
	Width W2 (Metric)	9.0mm
	Width W3 (Imperial)	0.2"
	Width W3 (Metric)	5mm
	Height H (Imperial)	0.04"
	Height H (Metric)	1.2mm
	Height H2 (Imperial)	0.27"
	Height H2 (Metric)	6.9mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	3.5mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	34.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.7mm
	Mounting Hole Diameter D (Imperial)	0.17 - 0.2"
	Mounting Hole Diameter D (Metric)	4.5 - 5.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.177"
	Mounting Hole Diameter D Max. (Imperial)	0.197"
Thickness T (Imperial)	0.043"	
Thickness T (Metric)	1.1mm	
Material and Specifications		
	Material	Polyamide 4.6 (PA46)
	Material Shortcut	PA46
	Material Cable Tie	Polyamide 4.6 (PA46)
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes

150-55948



Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	1.2kg