

EB-9000S-2 CURIE HEAT TECHNOLOGY SOLDERING/REWORK STATION

EB-9000S-2 FEATURES

- LCD display showing power demand from tip
- A slim soldering handpiece with comfortable grip and unique design for achieving a balanced “tip to grip” ratio.
- Improved cartridge design to ensure optimum tip performance and recovery.
- Increased plating to balance tip life and performance
- Gold plated connector for higher conductivity
- Color bands that provide for easy temperature identification and assist in audit and inventory control.
- Two switchable soldering ports
- Certified in accordance with TUV, CE & GS standards.

WARRANTY

All equipment and accessories are warranted to be free from defects in materials and workmanship:

Part Number	Description	Warranty Period
EB-9000PS-2	220-240V Power Supply	4 Years
SHP-1	Handpiece	90 Days
SHH-1	Workstand	90 Days



EB-9000S-2 COMPONENTS

EB-9000PS-2	Power Supply
SHH-1	Soldering Handpiece Holder
SHP-1	Soldering Handpiece
RMP-1	Tip Removal Pad
SG-1-GR	Handpiece Grip Green
SG-1-GY	Handpiece Grip Gray
BC-1	Brass Curls
SPG-1	Sulphide Free Sponge
EBM8CH176	Soldering tip cartridge

EB-9000S SPECIFICATIONS

Input Line Voltage:	EB-9000S-2	220-240 VAC
Tip to Ground Potential:		<2mV, true RMS 50-500Hz
Tip to Ground Resistance:		<2 Ohms DC
Idle temperature Stability:		+/- 1.1°C (2°F)
Ambient Operating Temperature:		10-40°C (50°F -104°F)
Maximum Enclosure Temperature:		50°C (122°F)
Fuse:	EB-9000S-2	250V 0.5A
Output Power (Maximum):		40 Watts
Output Frequency:		13.56 MHz
Size (W x H x D):		212.4mm x 118mm x 132mm
Weight:		3.47 KG
LCD display:		60mm x 16mm
Input Line Frequency:		50/60 Hz
Certification marks:		CE, GS

